

Specifications — RCP 2000 Remote Control Panel

Control/remote — control panel

Serial control port	RS-232, 9-pin female D connector
Baud rate and protocol	9600, 8-bit, 1 stop bit, no parity
Serial control pin configurations	2 = TX, 3 = RX, 5 = GND
Ethernet control port	1 RJ-45 female connector
Ethernet data rate	10/100Base-T, half/full duplex with autodetect
Ethernet protocol	ICMP (ping), TCP/IP, Telnet
Program control	Extron's control program for Windows® Extron's Simple Instruction Set (SIS™) Microsoft Explorer, Netscape Navigator, Telnet

General

Power	100VAC to 240VAC, 50/60 Hz, 60 watts, internal, autoswitchable
Temperature/humidity	Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, noncondensing Operating +32° to +122°F (0° to +50°C) / 10% to 90%, noncondensing
Rack mount	No
Enclosure type	Metal
Enclosure dimensions	5.5" H x 17.0" W x 12.0" D 14.0 cm H x 43.2 cm W x 30.5 cm D (Depth excludes connectors and knobs.)
Product weight	15 lbs (6.8 kg)
Shipping weight	22 lbs (10 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL
Compliances	CE, FCC Class A, VCCI, AS/NZS, ICES
MTBF	30,000 hours
Warranty	3 years parts and labor

NOTE *Specifications are subject to change without notice.*

(7.50+-051004-D4)